







Cab Control™

DIGI*STAR

The ration created. The ration fed. The ration they ate. PRECISELY.

ACCURATE | EASY | MANAGEMENT



Precision Feed Management Solutions

Cab Control™ is a wireless remote display and control system installed in the loader cab, that works seamlessly with the mixer scale indicator. There is no need to leave the loader cab during loading. The view of weight and information will not be affected by rain, snow, dirt, or darkness. You can view Recipe, Resize, and more and control the standard scale functions. With this system overloading of key ingredients is reduced.



Cab Control™ Touch CCT 400 & CCT 500

- Easily view and control scale indicator display remotely from inside the loader
- Simple to learn, more intuitive, graphic touch screen display
- Increased mounting opportunities in smaller cabs of skid steer and telescopic loaders and minimizes view obstruction from the slim, compact design
- Clearly indicates when call weight is reached with display color change in addition weight at zero
- Wearing gloves does not impede use due to advanced touch screen technology

Digi-Star International

Digi-Star Europe B.V.

J. F. Kennedylaan 235

NL - 5981 WZ Panningen, The Netherlands

Tel: +31 (0)77 462 92 64, E-mail: dsinfo@digi-star.com

www.digi-star.com www.tmrtracker.com

Cab Control™ App

Cab Control Functionality on a Smartphone or Tablet

- Easily view and control scale indicator display remotely from Android and iOS phone or tablet
- Simple to learn, intuitive, graphic touch screen display & control
- Provides same functionality as Digi-Star's other Cab Control systems: Net/Gross, Tare, Zero, Advance Ingredient, and Select Mixer
- Available free-of-charge from Play Store or iSTORE



Cab Control™

CC 400, CC 2.4, or CC 900

- Tare Key and Net/Gross Key allow for quick display viewing
- Four mounting bracket options: standard, wedge, u-bolt, and RAM for greater flexibility
- Front panel programmability for basic set-up calibration
- Backlit display

Cab Control™ benefits:

- Accurate loading
- Reduces overloading
- No need to leave the cab during loading
- Increases efficiency